

Manual sealless steel strapping tool with MicroLock™

**Characteristics**

Strapping qualities:	Uniflex and Ultraflex max. 1100 N/mm ² / 160'000 psi
Strapping dimensions:	widths 9.5 – 20.0 mm / ³ / ₈ – ³ / ₄ "
	thicknesses 0.38 – 0.63 mm / .015 – .025"
Weights:	4.45 kg / 9.8 lbs Normal-version
	4.7 kg / 10.4 lbs TW-version
Sealless joint:	Fromm MicroLock™
Average seal strength:	approx. 80 %
TW-version available:	Torque wrench tensioning system
Suspension (Optional):	Suspension for vertical and horizontal applications; has to be ordered separately
	Handle for horizontal applications; has to be ordered separately

Advantages

- The MicroLock™ sealless system guarantees a maximum of security of the sealless steel strapping joint against unlocking
- The tool can handle regular duty and high tensile steel strapping
- The tool can handle steel strapping up to a thickness of 0.64 mm / .025"
- Thanks to the special tensioning system (free wheeling) no loss of strap tension
- The sealing mechanism is completely closed
- The adjustment of the cutting and sealing depth is simple
- The feed wheel and the die and cutter support are easy to change

Chart of types model A337

Item No.	Model	Uniflex and Ultraflex max. 1100 N/mm ² / 160'000 psi			
		Width		Thicknesses	
		mm	inch	mm	inch
13.1850	A337/9.5/0.38-0.50	9.5	3/8"	0.38-0.50	.015-.020
13.1860	A337/10/0.38-0.50	10		0.38-0.50	.015-.020
13.1870	A337/12.7/0.38-0.50	12.7	1/2"	0.38-0.50	.015-.020
13.1872	A337/12.7/0.50-0.63	12.7	1/2"	0.50-0.63	.020-.025
13.1880	A337/13/0.38-0.50	13		0.38-0.50	.015-.020
13.1882	A337/13/0.50-0.63	13		0.50-0.63	.020-.025
13.1890	A337/16/0.38-0.50	16	5/8"	0.38-0.50	.015-.020
13.1892	A337/16/0.50-0.63	16	5/8"	0.50-0.63	.020-.025
13.1910	A337/19/0.38-0.50	19	3/4"	0.38-0.50	.015-.020
13.1912	A337/19/0.50-0.63	19	3/4"	0.50-0.63	.020-.025
13.1920	A337/20/0.38-0.50	20		0.38-0.50	.015-.020
13.1922	A337/20/0.50-0.63	20		0.50-0.63	.020-.025

Chart of types model A337 with torque wrench tensioning system

Item No.	Model	Uniflex and Ultraflex max. 1100 N/mm ² / 160'000 psi			
		Width		Thicknesses	
		mm	inch	mm	inch
13.1851	A337/9.5/0.38-0.50/TW	9.5	3/8"	0.38-0.50	.015-.020
13.1861	A337/10/0.38-0.50/TW	10		0.38-0.50	.015-.020
13.1871	A337/12.7/0.38-0.50/TW	12.7	1/2"	0.38-0.50	.015-.020
13.1873	A337/12.7/0.50-0.63/TW	12.7	1/2"	0.50-0.63	.020-.025
13.1881	A337/13/0.38-0.50/TW	13		0.38-0.50	.015-.020
13.1883	A337/13/0.50-0.63/TW	13		0.50-0.63	.020-.025
13.1891	A337/16/0.38-0.50/TW	16	5/8"	0.38-0.50	.015-.020
13.1893	A337/16/0.50-0.63/TW	16	5/8"	0.50-0.63	.020-.025
13.1911	A337/19/0.38-0.50/TW	19	3/4"	0.38-0.50	.015-.020
13.1913	A337/19/0.50-0.63/TW	19	3/4"	0.50-0.63	.020-.025
13.1921	A337/20/0.38-0.50/TW	20		0.38-0.50	.015-.020
13.1923	A337/20/0.50-0.63/TW	20		0.50-0.63	.020-.025

TW = Torque wrench tensioning system

Accessories

- A33.0121 Suspension for vertical and horizontal applications
- A33.0122 Handle for horizontal applications