



**Chart of types strapping head MH600**

Item No.	Model	Strap widths		Strap thicknesses		Max. Tension	
		mm	inch	mm	inch	N	lbs
47.5601	MH600/13-19/0.64-0.75/7.0/PET	13-19	½-¾	0.64-0.75	.025-.030	7000	1570
47.5602	MH600/13-19/0.80-1.35/7.0/PET	13-19	½-¾	0.80-1.35	.031-.053	7000	1570
47.5603	MH600/13-19/0.64-0.75/2.5/PET	13-19	½-¾	0.64-0.75	.025-.030	2500	560

**Features**

- Compact and modular design
- One piece of aluminium cast housing
- High strap tension up to 7000N (1570 lbs) adjustable
- Wide strap width range without changing parts
- Strap guide open feature
- Well proven friction weld sealing system
- High consistent seal efficiency because of environment temperature monitoring
- Dust cleaning system
- Three side suspension point for easy integration

**Options**

- De-coiler for Jumbo-coils
- Sword
- Telescopic insertion frame
- Movable machine
- Side sealing machine
- Head suspension with floating system
- Edge protection feed systems top and bottom
- Timper press system with various magazines
- Vertical and lateral press systems up to 80 KN
- Conveying systems
- Turntable for cross strapping
- Mechanical pack height sensor
- Re-inforced base plate