

Pneumatic sealless plastic strapping tool for heavy strapping**Characteristics**

Strapping qualities:	Polyester (PET)
Strapping dimensions:	widths 19.0 – 32.0 mm / 3/4 – 1 1/4"
	thicknesses 0.60 – 1.53 mm / .024 – .060"
Weight Incl. bracket:	8.5 kg / 18.7 lbs
Dimension without bracket:	L373 x W162 x H146 mm / 14.7" x 6.4" x 5.7"
Average seal strength:	approx. 75% (dependent on strap quality)
Type of seal:	Friction weld sealing
Strap tension:	2300 – 4000 N / 515 – 900 lbs (adjustable) ou 4000 – 7000 N / 900 – 1570 lbs (adjustable)
Tensioning speed:	135 mm/s / 5.3 inch/s ou 77 mm/s / 3.0 inch/s
Max. air pressure:	6.0 bar / 87 psi
Suspension bracket supplied with the tool	

Advantages

- Unique plastic strapping tool on the market
- The strapping tool can be used in two button (manual) or in one button operation mode (semi-automatic) by turning the adjustment screw for operation mode
- High tension force up to 7000 N
- Ideal for heavy duty applications with strapping dimensions of 19 to 32 mm (3/4 to 1 1/4) and a thickness up to 1.53 mm (.060")
- Pneumatically powered reliable and service friendly tool
- The strap tension can be adjusted individually using the adjustment system – thus the package is secured with a perfectly tensioned strap
- The sealing time is set individually for a specific strap quality and thickness and high seal strength is assured

Chart of types model P356

Item No.	Model	Strap widths		Strap thicknesses		Max. Tension		Tension speed	
		mm	inch	mm	inch	N	lbs	mm/sec.	inch/sec.
49.0503	P359/19/0.80-1.53/4.0	19	3/4	0.80-1.53	.031-.060	4000	900	135	5.3
49.0504	P359/19/0.80-1.53/7.0	19	3/4	0.80-1.53	.031-.060	7000	1570	77	3.0
49.0511	P359/25/0.60-0.79/4.0	25	1	0.60-0.79	.024-.030	4000	900	135	5.3
49.0512	P359/25/0.60-0.79/7.0	25	1	0.60-0.79	.024-.030	7000	1570	77	3.0
49.0513	P359/25/0.80-1.35/4.0	25	1	0.80-1.35	.031-.053	4000	900	135	5.3
49.0514	P359/25/0.80-1.35/7.0	25	1	0.80-1.35	.031-.053	7000	1570	77	3.0
49.0521	P359/32/0.60-0.79/4.0	32	1 1/4	0.60-0.79	.024-.031	4000	900	135	5.3
49.0522	P359/32/0.60-0.79/7.0	32	1 1/4	0.60-0.79	.031-.053	7000	1570	77	3.0
49.0523	P359/32/0.80-1.35/4.0	32	1 1/4	0.80-1.35	.024-.053	4000	900	135	5.3
49.0524	P359/32/0.80-1.35/7.0	32	1 1/4	0.80-1.35	.024-.053	7000	1570	77	3.0