

**Semi-automatix stretch wrapper economic FS390**

---

Semi-automatic stretch wrapper integrating 30 programs wrapping, equipped with two engines for the pre-stretching system.

**Features**

---

Diameter of turntable	Ø 1 650 mm
Weight of the pallet	2 000 kg
Standard height of the pallet	2 500 mm
Power supply	230V – 50 / 60 Hz 110V – 50 / 60 Hz

## Benefits

---

- Simple programming of wrapping for all dimensions of pallets and loads
- Certified CE
- Change film fast and simple
- Unité Unit motorized pre-stretching (two independent motors) to achieve a more than 400% pre-stretching (1 meter becomes 5 metres)
  - ⇒ Reduced film consumption
  - ⇒ Best qualities of film depending on the needs and, if necessary, to better stabilize the pallets
- Option to secure wrapping using a password setting
- Program to include the wrapping of the pallet feet
- Easy machine Maintenance

## Functions can be adjusted by the operator with password lock panel

- The adjustable film in 4 positions on the same pallet Tension
- Pre-stretching adjustable in 4 positions on the same palette
- The turntable speed adjustable 4 times
- Higher RPM / lower
- Speed of ascent / descent of the chariot in film
- Timed setting of the outbreak of the photoelectric cell for higher wrapping extra
- Program foot of pallet
- If necessary additional superior wrapping height
- Position on / off
- Operating in languages as Standard Instructions
- Ability to introduce 30 specific banding programs
- Program "multi-layer"
- Alarm messages reading ease

## Options

---

Turntable	1 500 mm, 1 800 mm, 2 200 mm
Open turntable (Horseshoe)	1 650 mm
Height of pallet	2 150 mm, 2 800 mm, 3 100 mm
Tray presser	
Access ramp	
Framework for integration in the soil	
Film cutting unit	
Photocell for detection black film	