

Wrapper semi-automatic FS110 / FS130 « CENTO » : the economic solution

**Features**

MACHINE

Diameter of turning table	Ø 1 500 mm
	Chain driven
Loading capacity	1 200 kg
Power supply	230V, 50/60Hz, 1 kW, 10A
Working conditions	5 ~ 45°C
Other	Rotation speed controlled by frequency inverter
	Patented exact position stop
	Automatic programs, parameters can be adjusted

CHARIOT

Mandrin	Ø 76 mm
Epaisseur de film	9 à 35 µm
Hauteur max. de palettes	2 100 mm
Autres	Patented mechanical brake system
	Photocell for pallet height detection
	Speed controlled by frequency inverter
	Film overlap can be regulated

Benefits

- Economic Solution against manual wrapping
- Certified CE
- Recognized quality
- Ideal for the packaging of small volumes in palette
- Ease of use - no special training required
- Connection 'Plug and Play' simplicity - no additional costs linked to the installation

Options for FS110 / FS130

- Loading ramp
- Photoelectric cell for dark loads
- Pit-option for floor installation
- ø 1 650 mm diameter of turning table, load capacity of 1 350 kg, chain driven
- ø 1 650 mm diameter of turning table, load capacity of 2 000 kg chain driven