

## Manual plastic strapping tools

---



### Characteristics

---

Strapping qualities:	Polypropylene (PP) and Polyester (PET)
Strapping dimensions:	widths 15.0 – 16.0 mm / $\frac{5}{8}$ "
thicknesses	0.50 – 0.90 mm / .020 - .035"
Weights:	3.8 kg / 8.4 lbs without suspension
	3.9 kg / 8.6 lbs with suspension
Average seal strength:	approx. 70 %
Type of joint:	Joint with special seals
Suspension (Optional):	bolt and grip ball for horizontal applications; have to be ordered separately

### Advantages

---

- Handy light weight tensioning and sealing tool to strap flat packages (i.e. pallets, bales, crates, cases, various packages) using plastic strapping
- A reliable, robust and service – friendly tool
- The windless tensioning system allows very high strap tension
- Special serrated seals and the patented sealing force balance system guarantee a very high seal joint efficiency
- The sealing handle is always operated until it hits the stop – thus the seal efficiency of all joints is high and balanced

**Chart of types model P404**

---

Item No.	Model	Width		Thicknesses	
		mm	inch	mm	inch
43.0404	P404/15-16/0.50-0.90	15-16	1/2"	0.50-0.90	.020-.035

**Seals**

---

Item No.	Model	Width		Contents of carton in pcs.	Weight	
		mm	inch		kg	lbs
41.5082	P404/16	15-16	5/8"	1000	9.3	20.5

**Accessories**

---

P40.2046 Handle for horizontal applications  
(Grip ball and bolt)