

Battery powered plastic strapping tool



Characteristics

Strapping qualities:	Polyester (PET) et Polypropylene (PP) plain and embossed
Strapping dimensions:	Width 12.0 – 16.0 mm / 7/16 – 5/8" Thickness 0.40 – 1.05 mm / .016 – .041"
Weight (incl. battery):	4.2 kg / 9.3 lbs
Tool size with battery:	L 351 x l 134 x H 143 mm / 13.8" x 5.3" x 5.6"
Type of seal:	Friction weld sealing
Average seal strength:	approx. 75% (dependent on strap quality)
Tension force:	250 – 2600 N / 56 – 585 lbs (adjustable)
Tension speed:	67 – 124 mm/s / 2.6 – 4.9 inch/s
Power supply:	Battery Li-Ion 18VDC / 4.0 Ah
Suspension bracket:	(optional)

Advantages

- High tension force up to 2600N / 585 lbs
- Tension force and sealing time adjustable with simple knobs
- Tool in both semi-automatic an automatic (single button) version available for efficient operation
- Brushless motor for less maintenance and improved life time
- Improves plates and guides - less effort to remove the tool from the strap
- No tension rocker – easier to remove tool from small package surfaces
- Motor temperature monitoring to protect motor from overheating
- Cycle counter included (special reader required)
- Battery well protected
- Battery charge indicator included
- Simple one-handed operation
- Tool is fully covered for finger protection
- Optional motor cooling fan available to reduce overheating risk

Accessories

P32.0223	Suspension bracket
P32.0224	Wearing plate (metal) for rough and hard surfaces
P32.0225	Protection plate (plastic) to protect complete bottom side
P32.0228	Motor cooling fan
N7.5154	Cycle count reader

Chart of types model P328

Item No.	Model	Strap widths		Strap thicknesses		Max. Tension		Tension speed	
		mm	inch	mm	inch	N	lbs	mm/sec.	inch/sec.
43.2422	P328/12/0.65-1.05	12		0.65-1.05	.026-.041	2600	585	67-124	2.6-4.9
43.2423	P328/12.7/0.4-0.64	12.7	½"	0.40-0.64	.016-.025	2600	585	67-124	2.6-4.9
43.2424	P328/12.7/0.65-1.05	12.7	½"	0.65-1.05	.026-.041	2600	585	67-124	2.6-4.9
43.2432	P328/13/0.65-1.05	13		0.65-1.05	.026-.041	2600	585	67-124	2.6-4.9
43.2453	P328/15.5/0.4-0.64	15.5		0.40-0.64	.016-.025	2600	585	67-124	2.6-4.9
43.2454	P328/15.5/0.65-1.05	15.5		0.65-1.05	.026-.041	2600	585	67-124	2.6-4.9
43.2461	P328/16/0.4-0.64	16	5/8"	0.40-0.64	.016-.025	2600	585	67-124	2.6-4.9
43.2462	P328/16/0.65-1.05	16	5/8"	0.65-1.05	.026-.041	2600	585	67-124	2.6-4.9
43.2622	P328/12/0.65-1.05/A	12		0.65-1.05	.026-.041	2600	585	67-124	2.6-4.9
43.2623	P328/12.7/0.4-0.64/A	12.7	½"	0.40-0.64	.016-.025	2600	585	67-124	2.6-4.9
43.2624	P328/12.7/0.65-1.05/A	12.7	½"	0.65-1.05	.026-.041	2600	585	67-124	2.6-4.9
43.2632	P328/13/0.65-1.05/A	13		0.65-1.05	.026-.041	2600	585	67-124	2.6-4.9
43.2653	P328/15.5/0.4-0.64/A	15.5		0.40-0.64	.016-.025	2600	585	67-124	2.6-4.9
43.2654	P328/15.5/0.65-1.05/A	15.5		0.65-1.05	.026-.041	2600	585	67-124	2.6-4.9
43.2661	P328/16/0.4-0.64/A	16	5/8"	0.40-0.64	.016-.025	2600	585	67-124	2.6-4.9
43.2662	P328/16/0.65-1.05/A	16	5/8"	0.65-1.05	.026-.041	2600	585	67-124	2.6-4.9

A = Automatic Model
Battery chargers for model P328

Item. No.	Model	Voltage / frequency	Countries
N5.4443	Li-Ion battery charger	220-240 V / 50-60 Hz	A, B, BG, BIH, BOL, BR, BY, CH, CL, CZ, D, DK, DZ, E, EAS, EST, ET, F, FIN, GE, GR, H, HK, HR, I, IL, IND, IR, IRQ, IS, JOR, KSA, KWT, L, LAR, LT, LV, MA, MC, MK, MOC, N, NL, P, PK, PE, PL, PRC, PY, RA, RCH, RI, RL, RO, ROK, ROU, RP, RUS, S, SK, SLO, SYR, THA, TN, TR, UA, UAE, YU, YV, (BRN), (BRU), (CY), (EAK), (EAT), (GB), (IRL), (M), (MAL), (OM), (SGP), (Y), (Z), (ZA), (ZW)
N5.4447	Li-Ion battery charger	120 V / 50-60 Hz	BR, C, CDN, CO, CR, DOM, EC, GCA, J, JA, KSA, LB, MEX, NIC, PA, Puerto Rico, RC, RP, USA, YV
N5.4445	Li-Ion battery charger	220-240 V / 50-60 Hz	AUS, NZ

(..) = Adapter N52.2102 required

Battery for model P328

Items. No.	Model	Voltage	Capacity	Charging time
N5.4349	Accu Li-Ion	18VDC	4.0 Ah	approx. 80 min.